



# GV / GO

120 150 200

## High capacity and performance

The new LIKE line of electricity-fired storage heaters of high capacity is designed and produced according to the most up-to-date European standards of efficiency, insulation and design.

### LT 150-200

- Steel boiler treated with thermosetting resins or with opal glass to ensure maximum purity of the water contained and the durability of the appliance.
- Insulation in foam polyurethane.
- Safety valve.
- Electric unit of 1200W with adjustable internal thermostat (1200W Horizontal model).

LIKE ELECTRICITY-FIRED



	Capacity	Power	Voltage	Heating time $\Delta t=50^{\circ}\text{C}$	Max operating temperature	Max operating press.	Net weight	Surface area of coil exchanger	Hydraulic connections	Coil connec- tions	A	B
	l	kW	V~	min	$^{\circ}\text{C}$	Mpa	kg	$\text{m}^2$	KW-WW	PV-PR	mm	mm
GV 120	120	1,5	230	295	75	0,8	29	-	R ½"	-	-	-
GV 150	150	2,0	230	280	75	0,8	42	-	R ¾"	-	945	500
GV 200	200	2,0	230	368	75	0,8	51,5	-	R ¾"	-	1205	800
GV/T 120	120	1,5	230	295	75	0,8	37,0	0,6	R ½"	Rp ½"	-	-
GV/T 150	150	2,0	230	280	75	0,8	56,5	0,9	R ¾"	Rp ½"	945	500
GV/T 200	200	2,0	230	368	75	0,8	66,0	0,9	R ¾"	Rp ½"	1205	800

MODEL 120

MODEL 150/200

